G-FLEX MEMBRANE

G-Flex Uncoupling Membrane Physical Properties.

PHYSICAL PROPERTIES	VALUE
Fleece raw material	PP
Core raw Material	HDPE
Color	Red
Material thickness	0,5 mm
Membrane thickness	3 mm
Weight	0,625 kg/m²
Air gap volume	1,6 L/m²
Stud cavities volume	1,2 L/m²
Shear strength (Pull-out test) Thinset tile adhesive - 28 days	>0.4 Mpa
Tear strength MD/CMD	>7/7 kN/m
Elongation	>25%
Performance temperature range	-30°C /+ 80°C

G-Flex Uncoupling Membrane Service rating Robinson test

FLOOR SYSTEM	RATING
Wood substrate 41 cm o.c.	EXTRA HEAVY
Wood substrate 49 cm o.c.	EXTRA HEAVY
Concrete slab	EXTRA HEAVY

G-Flex Uncoupling Membrane roll sizes

G-Flex 14 Roll 1 m x 14 m = 14 m²
G-Flex 30 Roll 1 m x 30 m = 30 m²

ESTIL GURÚ S.L.U.
P.I. El Pla Carrer dels telers, 22 - Apdo. 584
46870 ONTINYENT · Valencia · España
www.estilguru.com | guru@estilguru.com
Tel. 0034 96 291 45 11 | Fax. 0034 96 236 90 10