

W-S Band

Self-adhesive band

Autoadhesiva

Description Self-adhesive waterproofing membrane band manufactured with WATER-STOP. It offers an easier and faster alternative to other conventional solutions.

Features Excellent adhesion on approved substrates
Installation without the use of mortar
No waiting times

Technical data Size: 12,5 cm x 20 m



Manufacturer Estil Guru S.L.U

P.I. El Pla C/ Telers, 22 - Apdo. 584, 46870, Ontinyent,
Valencia, SPAIN | www.estilguru.com | guru@estilguru.com
Tel. 0034 96 291 45 11 | Fax. 0034 96 236 90 10

Product

Ref.	Description	Dimensions
IGU6031	W-S Band Autoadhesiva	12,5 cm x 20 m

Application areas:

W-S Band Autoadhesiva is suitable for the following intended uses:

- » For bonding on low-adhesion surfaces such as metals and plastics.
- » Bonding of WATER-STOP waterproof membrane or between W-S BOARD panels, in installations without water pressure.
- » Covering metal washers and joints between W-S BOARD and W-S NICHE.
- » DO NOT use at floor-to-wall junctions or in corners.

W-S Band

Self-adhesive
band

Autoadhesiva

Test table

Features	Method	Unit	Value
Watertightness	EN 1928	-	Pass
Reaction to fire	EN 13501-5	Class	E
Tensile properties:			
Tensile strength: L // T*1	EN 12311-2(A)	N/50 mm	≥100 // ≥100
Elongation: L // T	-	%	≥150 // ≥80
Resistance to static load	EN 12730 (B)	Kg	≥20
Impact resistance	EN 12691 (A)	mm	≥200
Lap-joint resistance:			
Peel resistance	EN 12316-2	N/50 mm	PND
Shear resistance	EN 12317-2	N/50 mm	PND
Low-temperature foldability	EN 495-5	°C	-20
UV + temperature + water exposure	EN 1297	Class	PND
*1 Test direction: L - longitudinal // T - transverse			

Technical drawings (cm)

