

DECLARATION OF PERFORMANCE

Nº DP001-WS270-V10613

1. Unique identification code of the product-type: WATER-STOP

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
See WATER-STOP stated on packaging and production details printed on the product.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Plastic membrane (EVA C) with non-woven on both sides for waterproofing floors and walls underneath flooring and wall covering in wet areas inside or outside. Installation: under tiling and bonded by thin set tile adhesive.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

ESTIL GURU S.L.U.

Polígono Industrial El Pla - C/ Telers, 22

46870 Ontinyent - Valencia.

Tel. 0034 96 291 45 11

guru@estilguru.com

Factory code: 966-J.

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): It does not apply

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: 2+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 13956:2012, Notified body No. 0799 - KIWA MPA Bautest Greven performed initial inspection of the manufacturing plant and of factory production control and continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued Certificate of Conformity of the Factory Production Control 0799-CPR-148.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **It does not apply**

9. Declared performance:

Essential Features		Performance		Harmonised Technical Specification
Property	Method	Unity	Value	
Watertightness	EN 1928	-	Pass	
Reaction to fire	EN 13501-5	Class	E	
Tensile strength (MD // CMD) *1				
Maximal tensile force (MD // CMD)	EN 12311-2 (A)	N/50 mm	≥200 // ≥200	
Elongation (MD // CMD)		%	≥20 // ≥10	
Resistance to root penetration			NDP	
Resistance to static loading	EN 12730 (B)	kg	≥20	EN 13956:2012
Resistance to impact	EN 12691 (A)	mm	≥500	
Resistance to tearing (MD // CMD)	EN 12310-2	N	NDP	
Join resistance				
Join peeling resistance	EN 12316-2	N/50 mm	NDP	
Join shear resistance	EN 12317-2	N/50 mm	≥230	
Flexibility at low temperature	EN 495-5	°C	-20	
UV stabilization + temperature + water	EN 1297	Class	NDP	

Dangerous substances :

This product does not contain any substances listed under REACH and does not require a Safety Data Sheet (SDS).

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Francisco Ferrándiz. Technical Manager.

Ontinyent, 1 July 2024.

