

Safetub

Adaptable reinforcement

Description

Accessory for sealing penetrations in waterproofing systems using WATER-STOP membrane. It consists of a WATER-STOP membrane integrated with a watertight elastomeric membrane.

Features

Compatible with WATER-STOP
Watertight seal between different materials
Suitable for different diameters
Resistant to temperature changes


Technical data

Width: 18 cm // 23 cm // 30,5 cm
Length: 18 cm // 23 cm // 30,5 cm
Diameter: Ø32-Ø50 // Ø63-Ø75 // Ø90-Ø128

Manufacturer

Estil Guru S.L.U

P.I. El Pla C/ Telers, 22 - Apdo. 584, 46870, Ontinyent,
Valencia, SPAIN | www.estilguru.com | guru@estilguru.com
Tel. 0034 96 291 45 11 | Fax. 0034 96 236 90 10



Product

Ref.	Description	Measures	Format
IG60020	Safetub	Ø 32-50	Bag - 5 pcs
IG60021	Safetub	Ø 63-75	Bag - 5 pcs
IG60022	Safetub	Ø 90-128	Bag - 5 pcs

Test table

Characteristics	Method	Unit	Tolerance	Value
Water tightness	EN 1928	-	-	Pass
Reaction to fire	EN 13501-5	Class	-	E
Tensile properties:				
Tensile strength: L // T^{*1}	EN 12311-2 (A)	N/50 mm	-	≥200 // ≥200
Elongation: L // T	EN 12311-2 (A)	%	-	≥50 // ≥80
Resistance to root penetration			-	PND
Resistance to static load	EN 12730 (B)	Kg	-	≥20
Impact resistance	EN 12691 (A)	mm	-	≥200
Overlap resistance:				
Peel resistance	EN 12316-2	N/50 mm	-	PND
Shear resistance	EN 12317-2	N/50 mm	-	PND
Low-temperature flexibility	EN 495-5	°C	-	-20
Appearance	-	Art. 4.1.2	-	-
UV exposure + temperature + water	EN 1927	Class	-	Pass

^{*1} Test direction: L - longitudinal // T - transverse